



## Universal manual Bonder & Tester 5600

### Bond / Tester System

<b>Testheads</b>	Pullheads – 100cN – 5000 cN
	Shearheads – 500cN – 50000 cN
	Tweezerhead – 100cN
<b>Bondheads</b>	5610, 5630, 5632, 5650, 5650HR

### Bonder / Tester Base

#### Axes

- Working area X/Y-axis 100x115mm
- Step resolution 0,25µm
- Repeatability <2µm

#### Hardware

- Dual Core PC, 1,6 GHz processor,
- 4 GB RAM, Ethernet, 4x USB-Hub Front
- Firewire CCD colour camera 1,4 MPixel
- Network-capable with TCP / IP server

#### Software

- Statistics such as mean value, standard deviation, trend, cp, cpk, etc. Based on SQL Databanc
- Export Format SQL, CSV, HTML

#### Speed

Test speed from 0.2 to 5mm/s

#### Dimenstions

W x D x H – 70 x 65x 70 cm, weight approx. 80kg

#### Connections

100–240 VAC, 1 Phase, 50/60 Hz, max 500 VA  
Ø 6mm standard vacuum tubing

### The 5600:

The manual bond tester 5600 complements F&S Bondtec Semiconductor GmbH die- and wire- bonders. The PC controlled moving table allows any number of bonds to be tested automatically from a stored program.


Results can be analysed and output immediately or exported in a number of data base formats for subsequent analysis as desired. Powerful extended capabilities enable measurements such as force/time or force/distance curves to be made and deliver more data about the quality of the bond tested.

Exchangeable measurement cartridges ensure rapid conversion to different force ranges. The calibration curves of all measurement cartridges are stored internally; additional heads for shear, peel and tweezer testing with customer-specific tools and jaws are available.


After a first programming a reproducible pull- or sheartest can be guaranteed for all following components.

## Workholder

Standard-Workholder  
for parts up to 4x4"  
with Vacuum und mechanical clamping




## Optional:



workholders up to 4x4"  
with jaws



TO workholder with  
mechanical clamping



4x4" workholder with .  
rubberized surface and  
mechanical clamping

### F&S Bondtec Semiconductor GmbH

Industriezeile 49a

A-5280 Braunau am Inn

Tel.: +43-7722-67052-8270

Fax: +43-7722-67052-8272

Mail: [info@fsbondtec.at](mailto:info@fsbondtec.at)

Web: [www.fsbondtec.at](http://www.fsbondtec.at)

**Hilpert**  
electronics

Ihr Vertriebspartner/ Votre représentant:

Hilpert electronics AG  
Täferstrasse 29  
5405 Baden-Dättwil  
Schweiz / Suisse

Tel: +41 56 483 25 25  
Fax: +41 56 483 25 20  
Mail: [office@hilpert.ch](mailto:office@hilpert.ch)  
Web: [www.hilpert.ch](http://www.hilpert.ch)

