

200mm Silicon Wafer Stock list (pg1)



Position	Diameter (mm)	Thickness (μm)	Type	Resistivity (Ω • cm)	Orientation (degree)	Notch (SEMI)	Surface Finish	Lasermark	Quantity
1	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	4925
2	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	12000
3	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	12000
4	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	500
5	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	4000
6	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	5500
7	200.0±0.2	725±25	P	1-20	100	Notch	SSP	None	350
8	200.0±0.2	725±25	N	>10000	100	Notch	SSP	None	250
9	200.0±0.2	725±25	Intrinsic	>10000	100	Notch	SSP	None	350
10	200.0±0.2	725±20	P	0.007-0.014	100	Notch	SSP	Backside	925
11	200.0±0.2	725±25	P	100-200	100	Notch	SSP	None	25
12	200.0±0.2	725±25	P	1-100	100	Notch	SSP	None	500
13	200.0±0.2	725±15	P	1-100	100	Notch	SSP	None	175
14	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	50
15	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	25
16	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	4350
17	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	25
18	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	1400
19	200.0±0.2	725±25	N	10-20	100	Notch	SSP	None	25
20	200.0±0.2	725±25	N	10-20	100	Notch	SSP	None	425
21	200.0±0.2	725±15	P	10-20	100	Notch	DSP	None	300
22	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	200
23	200.0±0.2	725±15	P	10-20	100	Notch	SSP	None	150
24	200.0±0.2	725±15	P	10-20	100	Notch	SSP	Backside	125
25	200.0±0.2	735±15	P	0.01-0.02	100	Notch	SSP	Backside	325

26	200.0±0.2	735±15	P	0.01-0.02	100	Notch	SSP	Backside	650
27	200.0±0.2	725±20	P	10-20	100	Notch	SSP	None	50
28	200.0±0.2	725±25	P	1-20	100	Notch	SSP	None	1,000
29	200.0±0.2	725±15	P	1-100	100	Notch	SSP	None	350
30	200.0±0.2	725±25	N	1-10	100	Notch	DSP	Backside	75
31	200.0±0.2	725±25	N	1-10	100	Notch	DSP	Backside	25
32	200.0±0.2	725±20	P	1-2	100	Notch	SSP	None	50